

16 Series Medium Heavy Duty Casters

Made in the **USA**

CAPACITY TO 1250




Premium Quality



Environmentally Friendly




MOUNTING OPTIONS Standard Plate




Special Order Plates

Optional D Plate



Optional K Plate



The 16 Series features a quality USA made rig and 3-year warranty, along with the most wheel and brake options in the industry. This quality lineup provides lasting value, all at a competitive price.

TYPICAL APPLICATIONS

- Shop/Distribution Carts
- Dollies
- Waste disposal trucks
- Warehouse trucks
- Floor Trucks

SWIVEL CROSS SECTION



+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Neoprene on Aluminum (28 Precision Ball Bearing)

NP	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
	5	2	600	6 1/2	15/8		16NP05228
	6	2	700	7 1/4	13/4		16NP06228
	8	2	700	9 1/2	13/4		16NP08228

Moldon Rubber on Cast Iron (01 Roller Bearing)

MR	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
	4	1 1/2	250	5 5/8	1 11/16	5 3/4	16MR04101
	4	2	300	5 5/8	1 11/16	5 1/4	16MR04201
	5	1 1/2	350	6 1/2	15/8	6	16MR05101
	5	2	450	6 1/2	15/8	5 1/2	16MR05201
	6	2	500	7 1/4	13/4	8	16MR06201
	8	2	600	9 1/2	13/4	10 1/4	16MR08201

Heavy Duty Moldon Rubber on Cast Iron (01 Roller Bearing)

MH	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
	3 1/4	1 1/2	340	4 1/4	1 3/4	4 1/2	16MH03101
	4	1 1/2	400	5 5/8	1 11/16	5 3/4	16MH04101
	5	2	700	6 1/2	15/8	5 1/2	16MH05201
	6	2	820	7 1/4	13/4	8	16MH06201
	8	2	1000	9 1/2	13/4	10 1/4	16MH08201

FEATURES

- All caster rigs and many wheels **now made in the USA**
- **3 Year warranty**
- **New upper/Lower Raceway Rubber seals:** Optional rubber swivel raceway seals help protect casters
- **Improved zinc plated finish** for attractive appearance, better corrosion resistance and longer caster life
- **Bigger kingpin:** New bigger, stronger 3/4" kingpin on standard top plate
- **Top Plate & Yoke Base:** Cold formed from 1/4" steel plate. Yoke base is notched for factory or field-installable 4-position swivel lock
- **Swivel Section:** Smooth formed, hardened double ball bearing raceways minimize ball indentation and wear
- **Fork Legs:** 1/4" steel, formed to increase strength and welded to yoke base
- **Axle:** 1/2" diameter hollow axle complete with lock nut with straight roller and Delrin bearings. Axle is solid with ball, plain bore, and Oilix bearings
- **Wheel seals:** Nylon seal retaining/thrust washers
- **Lubrication:** Zerk fitting in swivel section and in recessed head of hollow axle on straight roller and Delrin bearing wheels
- Alternate or custom caster configurations available

RIG OPTIONS

- King bolt and nut specify **KB16**
- Neoprene sealed swivel section specify **SS02**
- NSF Listed for food service industry specify **NSF**
- Notched seal kit specify **SD016001**
- Unnotched seal kit specify **SD016002**
- **Optional Overall Heights** see notes at end of 16 Series section
- **Stainless steel** versions available, see page 78-79

BRAKE OPTIONS

To order, add brake code below to end of model. Example: 16XS06201**ST**

Total Lock specify **T** (4" to 8" models) specify optional 7 1/2" (HS-60) overall height model if ordering 6"

Grip Lock specify **GL1**

Cam specify **CB1**

Face specify **FBA**

Face specify **FBB**

Single Side specify **SSB**. **Double Sided** specify **DSB**

Face specify **FBE**

Poly Cam specify **P**

Swivel Lock (welded) specify **L**

Hand operated field installable swivel lock order **SL160000** separately

Foot operated field installable swivel lock order **SL160002** separately

BEARING OPTIONS



Note: Wheel capacities can change with each bearing type. Consult factory.

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Moldon Rubber on Aluminum (01 Roller Bearing)

MD	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
	4	1 1/2	250	5 5/8	1 11/16	4 3/4	16MD04101
	5	1 1/2	300	6 1/2	15/8	5	16MD05101
	6	2	550	7 1/4	13/4	6	16MD06201
	8	2	600	9 1/2	13/4	6 1/2	16MD08201

Continue on next page >>

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Soft Rubber (01 Roller Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
RR	4	2	220	55/8	111/16	6	16RR04201
	5	2	325	61/2	15/8	6 1/2	16RR05201
	6	2	350	71/4	13/4	6 3/4	16RR06201

Monoprene Semi-Pneumatic (27 Radial Ball Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
SZ	6	2	250	71/4	13/4	5 1/2	16SZ06227
	8	2	280	91/2	13/4	6 1/2	16SZ08227

For grey tread specify "SV" wheel code (example 16SV05228).

Pneumatic (27 Radial Ball Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
SF	8	2	210	91/2	13/4	6 1/2	16SF08227

Eagle Polyurethane on Polypropylene (01 Roller Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
EG	4	2	600	55/8	111/16	5 3/4	16EG04201
	5	2	900	61/2	15/8	5 1/2	16EG05201
	6	2	1100	71/4	13/4	8	16EG06201
	8	2	1200	91/2	13/4	10 1/4	16EG08201

X-tra Soft (Flat Tread) (01 Roller Bearing)*

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
XS	4	2	350	55/8	111/16	5 1/4	16XS04201
	5	2	375	61/2	15/8	5 1/2	16XS05201
	6	2	600	71/4	13/4	6	16XS06201
	8	2	675	91/2	13/4	6 1/2	16XS08201

Prevenz™ antimicrobial models available (Add PREV).
*Precision Ball (28) and Delrin (51) Bearings available.
Change "01" to other bearing code. Precision Ball example: 16XS04228. Delrin example: 16XS04251.

X-tra Soft (Round Tread) (01 Roller Bearing)*

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
XR	6	2	450	71/4	13/4	5 1/2	16XR06201
	8	2	600	91/2	13/4	6 1/2	16XR08201

Prevenz™ antimicrobial models available (Add PREV).
*Precision Ball (28) and Delrin (51) Bearings available.
Change "01" to other bearing code. Precision Ball example: 16XR04228. Delrin example: 16XR04251.

Polypropylene (01 Roller Bearing)*

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PB	4	1 1/2	400	55/8	111/16	4 1/2	16PB04101
	4	2	450	55/8	111/16	4 1/2	16PB04201
	5	1 1/2	450	61/2	15/8	5	16PB05101
	5	2	550	61/2	15/8	5	16PB05201
	6	1 1/2	550	71/4	13/4	5 3/4	16PB06101
	6	2	750	71/4	13/4	6	16PB06201
	8	2	850	91/2	13/4	5 1/2	16PB08201

*Delrin (51) Bearings or plain bore (41) models available.
Change "01" to other bearing code. Delrin example: 16PB04251.

White Polypropylene (41 Plain Bore)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PW	4	2	450	55/8	111/16	4 1/2	16PW04241
	5	2	550	61/2	15/8	5	16PW05241
	6	2	650	71/4	13/4	6	16PW06241

High Temp Polypropylene (41 Plain Bore)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
RW	4	2	500	55/8	111/16	5	16RW04241
	5	2	650	61/2	15/8	5 1/2	16RW05241
	6	2	700	71/4	13/4	6	16RW06241
	8	2	900	91/2	13/4	6 1/2	16RW08241

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Polyurethane on Aluminum (01 Roller Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PD	4	1 1/2	600	55/8	111/16	4 1/2	16PD04101
	4	2	700	55/8	111/16	5	16PD04201
	5	1 1/2	720	61/2	15/8	5	16PD05101
	5	2	1050	61/2	15/8	5 1/4	16PD05201
	6	2	1230	71/4	13/4	5 3/4	16PD06201
	8	2	1250	91/2	13/4	7	16PD08201

Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
AX	4	2	700	55/8	111/16	5 1/2	16AX04228
	5	2	1000	61/2	15/8	6	16AX05228
	6	2	1250	71/4	13/4	7	16AX06228
	8	2	1250	91/2	13/4	9	16AX08228

85 Shore A

Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PM	5	2	1000	61/2	15/8	6	16PM05228
	6	2	1250	71/4	13/4	7	16PM06228
	8	2	1250	91/2	13/4	9	16PM08228

95 Shore A

Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PM 80A	5	2	1000	61/2	15/8	6	16PM0522880A
	6	2	1250	71/4	13/4	7	16PM0622880A
	8	2	1250	91/2	13/4	9	16PM0822880A

80 Shore A To Specify Rigid or Swivel, insert "R" or "S" before "80A".
Example: 16PY08228R80A.

Polyurethane on Cast Iron (01 Roller Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
PY	3 1/4	1 5/8	420	4 1/4	1 3/4	4 1/4	16PY03101
	4	2	750	55/8	111/16	7	16PY04201
	5	2	1050	61/2	15/8	8	16PY05201
	6	2	1200	71/4	13/4	9 3/4	16PY06201
	8	2	1250	91/2	13/4	10	16PY08201

80A Durometer available, add "80A" to end of caster number.
80A capacity reduced by approximately 20%.
Swivel example: 16PY06201S80A.

Polyurethane on Polypropylene (01 Roller Bearing)

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
XA	4	2	600	55/8	111/16	4 1/4	16XA04201
	5	2	750	61/2	15/8	4 3/4	16XA05201
	6	2	900	71/4	13/4	5 1/2	16XA06201
	8	2	1000	91/2	13/4	7 1/2	16XA08201

Prevenz™ antimicrobial models available.
Add PREV to end of caster number.

V-Grooved Solid Polyurethane (02 Drawn Cup Roller Bearing)*

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
XV	4	2	300	55/8	111/16	4 1/2	16XV04202
	5	2	300	61/2	15/8	5	16XV05202
	6	2	300	71/4	13/4	5 1/4	16XV06202
	8	2	300	91/2	13/4	5 3/4	16XV08202

*Delrin (52) Bearings models available.
Change "02" to other bearing code. Example: 16XV04252.

X-Treme™ Solid Polyurethane (01 Roller Bearing)*

	Wheel Diameter (inches)	Tread Width (inches)	Capacity (lbs) (Based on manual operation)	Overall Height (inches)	Swivel Lead (inches)	Approx. Wt. (lbs)	Base Caster Number+
XI	4	2	1000	55/8	111/16	5	16XI04201
	5	2	1000	61/2	15/8	5 1/2	16XI05201
	6	2	1000	71/4	13/4	6 1/4	16XI06201
	8	2	1000	91/2	13/4	8	16XI08201

*Drawn Cup Roller (02), Bronze (22), Pedestal Precision (28), and Delrin (51) bearings available. Change "01" to other bearing code. Pedestal Precision example: 16XI04229.

Continue on next page >>

Continued from previous page

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

X-Treme™ Plus Solid Polyurethane (01 Roller Bearing)*

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
XP	4	2	1250	55/8	111/16	5	16XP04201
	5	2	1200	61/2	15/8	51/2	16XP05201
	6	2	1250	71/4	13/4	61/4	16XP06201
	8	2	1250	91/2	13/4	8	16XP08201

*Drawn Cup Roller (02), Bronze (22), Pedestal Precision (29), and Delrin (51) bearings available. Change "01" to other bearing code. Pedestal Precision example: 16XP04229.

Phenolic (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
TM	31/4	11/2	600	41/4	13/4	41/2	16TM03101
	31/4	2	700	41/4	13/4	41/2	16TM03201
	4	11/2	600	55/8	111/16	41/2	16TM04101
	4	2	800	55/8	111/16	5	16TM04201
	5	11/2	600	61/2	15/8	51/4	16TM05101
	5	2	1000	61/2	15/8	51/4	16TM05201
	6	11/2	800	71/4	13/4	51/2	16TM06101
	6	2	1200	71/4	13/4	61/4	16TM06201
	8	2	1250	91/2	13/4	8	16TM08201

Straight Sided Phenolic (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
TH	4	2	1000	55/8	111/16	5	16TH04201
	5	2	1200	61/2	15/8	51/2	16TH05201
	6	2	1250	71/4	13/4	61/4	16TH06201

Maxim® (01 Roller Bearing)*

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
NG	31/4	2	700	41/4	13/4	5	16NG03201
	4	2	800	55/8	111/16	5	16NG04201
	5	2	1000	61/2	15/8	51/2	16NG05201
	6	2	1200	71/4	13/4	61/4	16NG06201
	8	2	1250	91/2	13/4	8	16NG08201

Prevenz™ antimicrobial models available. Add PREV to end of caster number.

*Drawn Cup Roller (02), Bronze (22), Pedestal Precision (29), and Delrin (51) bearings available. Change "01" to other bearing code. Pedestal Precision example: 16NG04229.

Glass Filled Polypropylene (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
RT	4	2	800	55/8	111/16		16RT04201
	5	2	1000	61/2	15/8		16RT05201
	6	2	1200	71/4	13/4		16RT06201
	8	2	1250	91/2	13/4		16RT08201

Heavy Duty Glass Filled Nylon (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
DT	4	2	800	55/8	111/16		16DT04201
	5	2	1200	61/2	15/8		16DT05201
	6	2	1250	71/4	13/4		16DT06201
	8	2	1250	91/2	13/4		16DT08201

High Temp Glass Filled Nylon (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
HT	4	2	800	55/8	111/16		16HT04201
	5	2	1000	61/2	15/8		16HT05201
	6	2	1200	71/4	13/4		16HT06201
	8	2	1250	91/2	13/4		16HT08201

Trionix™ High Impact Polymer (28 Precision Ball Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
NX	4	2	1250	55/8	111/16	7	16NX04228
	5	2	1250	61/2	15/8	8	16NX05228
	6	2	1250	71/4	13/4	93/4	16NX06228
	8	2	1250	91/2	13/4	10	16NX08228

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Solid Elastomer (28 Precision Ball Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
SE	4	2	1000	55/8	111/16	7	16SE04228
	5	2	1000	61/2	15/8	8	16SE05228
	6	2	1100	71/4	13/4	93/4	16SE06228
	8	2	1200	91/2	13/4	10	16SE08228

White Nylon (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
NW	5	2	600	61/2	15/8	6	16NW05201
	6	2	900	71/4	13/4	7	16NW06201
	8	2	1100	91/2	13/4	81/2	16NW08201

Cast Iron (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
CA	31/4	11/2	400	41/4	13/4	41/2	16CA03101
	31/4	2	700	41/4	13/4	63/4	16CA03201
	4	11/2	600	55/8	111/16	6	16CA04101
	4	17/8	1000	55/8	111/16	7	16CA04201
	5	11/2	600	61/2	15/8	63/4	16CA05101
	5	17/8	1250	61/2	15/8	8	16CA05201
	6	11/2	800	71/4	13/4	73/4	16CA06101
	6	17/8	1250	71/4	13/4	93/4	16CA06201
	8	2	1250	91/2	13/4	121/2	16CA08201

Heavy Duty Cast Iron (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
CH	5	2	1250	61/2	15/8	9	16CH05201
	6	2	1250	71/4	13/4	11	16CH06201
	8	2	1250	91/2	13/4	14	16CH08201

Dropped Forged Steel (01 Roller Bearing)*

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
FS	4	11/2	1250	55/8	111/16	7	16FS04101
	5	13/4	1250	61/2	15/8	83/4	16FS05201
	6	2	1250	71/4	13/4	93/4	16FS06201

*Tapered Roller bearings (09) available. Change "01" to other bearing code. (Example: 16FS04109).

V-Grooved Cast Iron (01 Roller Bearing)*

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
VG	4	2	800	55/8	111/16	7	16VG04201
	5	2	800	61/2	15/8	83/4	16VG05201
	6	2	1000	71/4	13/4	93/4	16VG06201

*Tapered Roller bearings (09) available. Change "01" to other bearing code. (Example: 16VG04109).

Ductile Iron Crowned Tread (01 Roller Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
FR, FM	5	2	1250	61/2	15/8	9	16FR05201
	6	2	1250	71/4	13/4	11	16FR06201
	8	2	1250	91/2	13/4	14	16FR08201

*Tapered Roller bearings (09) and Precision Ball (28) available. Tapered Roller example: 16FR05209.

Note: Ductile Iron Flat Tread (FM) models available. Change FR wheel code to FM. Example: 12FM05201.

Optional Overall Heights all 16 Series Models:

Wheel Dia.	Overall Height	Swivel Lead	Swivel Specify	Rigid Specify	Wheel Dia.	Overall Height	Swivel Lead	Swivel Specify	Rigid Specify
3-1/4"	5-1/4"	1-11/16"	HS42	HR42	6"	6-7/8"	2-1/2"	HS56	HR56
4"	5-1/4"	1-11/16"	HS86	HR86	6"	7-3/8"	1-3/4"	HS59	HR59
5"	6-1/8"	1-11/16"	HS50	HR50	6"	7-1/2"	1-7/8"	HS60	HR60
	6-3/4"	1-3/4"	HS54	HR54	8"	10"	1-3/4"	HS81	HR81