

Baron



Features

- Double ball bearing raceways
- Octagon washer on threaded stem for easy installation
- 2" model is heat treated

Wheel Selection



1-5/8" Spherical Soft Rubber

2" Spherical Polyolefin

Applications Store Fixtures

- Furniture
- Office Equipment
- Medical Equipment

Options

- RoHS compliant zinc
- finish available by special
- order; please consult
- factory for details.

Di	Nheel ameter nches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Material	Finish Type	Dynamic Load (Pounds)	Base Model # (Add fastening code)	Fastening Selection*
Γ	1-5/8"	2-5/16"	1-3/4"	Spherical Soft Rubber	Metalized Brass	70	PBH16MB-3RD	Threaded: 532, 507 Grip Neck: 302 Grip Ring: 223, 211 Plate: 113
					Windsor Antique	70	PBH16WA-3RD	
Γ	2"	2-5/8"	2-1/4"	Spherical Polyolefin	Bright Chrome	80	PBH20BC-3ED	Threaded: 532, 507, 634, 605
L					Metalized Brass	80	PBH20MB-3ED	Grip Neck: 302 Grip Ring: 222, 223, 211
L					Windsor Antique	80	PBH20WA-3ED	Plate: 113

*To order, include blue fastener code in Base Model Number. Example:PBH16507MB-3RD

Threaded				C	Grip Neck Grip Ring			Top Plate	
	532 —	— 507 -	<u> </u>	<u> </u>	<u> </u>	222 223	<u> </u>	——113	
•	3/4"↓ 5/16"	1"↓ 5/16"	1-1/2" UNC16 3/8"	1"↓ 3/8"	1-1/2" 5/16"	1"1 3/8" 7/8" 7/16"	1-7/16" 7/16"	⁵ 0 ¹ 0	

Finish Options





Windsor Antique



Bright Chrome

Socket Options

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.



Weldable

caster

mount



square tubes





225



Corner brackets

.