

DC

DC Dolly Casters

CAPACITY TO 350



FEATURES

- **Swivel Section:** Double ball raceway for standard top plate (Single ball raceway for optional S01 top plate)
- **Finish:** Zinc plated finish
- **Thread Guards:** Interlocking thread guards standard on XS models, keeping out entangling debris for longer life
- **Construction:** Riveted construction
- Alternate or custom caster configurations available

RIG OPTIONS

NSF: Consult factory

BRAKE OPTION

Face Contact specify F



BEARING OPTIONS


Annular Ball (31)
Plain (41)

An ideal solution for dolly applications; the DC Dolly lineup is both economical and durable. All wheels are non-marking, and the XS wheels feature interlocking thread guards to protect them from entangling debris.

TYPICAL APPLICATIONS


- Dolly carts
- Display carts

SWIVEL CROSS SECTION




MOUNTING OPTIONS

Standard Plate



Special Order Plates

S01 Top Plate for parts ending in S01



- Economical
- Non marking
- Thread guards protect axle from entangling debris

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+	
TPR Rubber (31 Annular Ball Bearing)	XS	3	1 1/4	275	3.8	1 1/4	.5	DCXS03031S01
		3	1 1/4	275	4 1/4	1 11/16	.5	DCXS03031
		3 1/2	1 1/4	300	4 3/4	1 11/16	.5	DCXS03X31
		4	1 1/4	325	5 1/4	1 11/16	.5	DCXS04031
		5	1 1/4	350	6 1/4	1 11/16	.5	DCXS05031

Non-marking TPR wheel (75 Shore A)

Polyurethane on Polypropylene (41 Plain Bearing)

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+	
XA		3	1 1/4	275	3.8	1 1/4	.5	DCXA03041S01
		3	1 1/4	275	4 1/4	1 11/16	.5	DCXA03041
		3 1/2	1 1/4	300	4 3/4	1 11/16	.5	DCXA03X41
		4	1 1/4	325	5 1/4	1 11/16	.5	DCXA04041
		5	1 1/4	350	6 1/4	1 11/16	.5	DCXA05041

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+	
Polypropylene (41 Plain Bearing)	PB	3	1 1/4	275	3.8	1 1/4	.5	DCPB03041S01
		3	1 1/4	275	4 1/4	1 11/16	.5	DCPB03041
		3 1/2	1 1/4	300	4 3/4	1 11/16	.5	DCPB03X41
		4	1 1/4	325	5 1/4	1 11/16	.5	DCPB04041
		5	1 1/4	350	6 1/4	1 11/16	.5	DCPB05041