

MOLD-ON RUBBER WHEELS

RWM rubber tread wheels are constructed by molding high quality rubber to cast iron cores. All RWM mold-on rubber wheels are floor protective, provide long tread life, are quiet in operation and are highly resilient. These wheels are suggested for use on all types of floors and numerous applications. The standard RWM mold-on rubber tread is 75 durometer Shore A.



RIR-0830-16

RIR-0820-08

FEATURES

Hardness	70-75 Shore A Durometer
Temperature Rating	-30° to 140°F continuous; 180°F intermittent.

APPLICATIONS

Trash containers	Lumber carts
Platform carts	Many manually-pushed low-cost applications

OPTIONS

SPANNERS

SI Spanner Included

LENGTH

YY Shorter Hub Length

Wheel Diameter	Wheel Width	Capacity lbs.	Axle Diameter	Roller Bearing	Tapered Bearing	Hub Length	Approx Weight lbs.
4"	1-1/2"	250	1/2"	RIR-0415-08		1-7/8"	1.2
		250	5/8"	RIR-0415-10		1-7/8"	1.2
		250	3/4"	RIR-0415-12		1-7/8"	1.2
4"	2"	350	1/2"	RIR-0420-08		2-7/16"	3.1
		350	5/8"	RIR-0420-10		2-7/16"	3.1
		350	3/4"	RIR-0420-12		2-7/16"	3.1
5"	1-1/2"	300	1/2"	RIR-0515-08		1-7/8"	2.0
		300	5/8"	RIR-0515-10		1-7/8"	2.0
		300	3/4"	RIR-0515-12		1-7/8"	2.0
5"	2"	400	1/2"	RIR-0520-08		2-7/16"	3.5
		400	5/8"	RIR-0520-10		2-7/16"	3.5
		400	3/4"	RIR-0520-12		2-7/16"	3.5
6"	1-1/2"	370	1/2"	RIR-0615-08		1-7/8"	2.3
		370	5/8"	RIR-0615-10		1-7/8"	2.3
		370	3/4"	RIR-0615-12		1-7/8"	2.3
6"	2"	410	1/2"	RIR-0620-08		2-7/16"	4.1
		410	5/8"	RIR-0620-10		2-7/16"	4.1
		410	3/4"	RIR-0620-12		2-7/16"	4.1
6"	2-1/2"	540	3/4"	RIR-0625-12-YY		3"	7.8
		540	1"	RIR-0625-16-YY		3"	7.8
		540	1"	RIR-0625-16-YY-SI		3"	7.8
		540	1-1/4"	RIR-0625-20-YY		3"	7.8
		540	3/4"	RIR-0625-12		3-1/2"	10.0
		540	1"	RIR-0625-16		3-1/2"	10.0
		540	1"	RIR-0625-16-SI		3-1/2"	10.0
		540	1-1/4"	RIR-0625-20		3-1/2"	10.0
		540	1-1/4"	RIR-0625-20		3-1/2"	10.0

 Wheel Diameter	 Wheel Width	 Capacity	 Axle Diameter	 Roller Bearing	 Tapered Bearing	 Hub Length	 Approx Weight
6"	3"	680	3/4"	RIR-0630-12		3-1/2"	11.2
		680	1"	RIR-0630-16		3-1/2"	11.2
		680	1"	RIR-0630-16-SI		3-1/2"	11.2
		680	1-1/4"	RIR-0630-20		3-1/2"	11.2
8"	2"	500	1/2"	RIR-0820-08		2-7/16"	6.3
		500	5/8"	RIR-0820-10		2-7/16"	6.3
		500	3/4"	RIR-0820-12		2-7/16"	6.3
8"	2-1/2"	670	3/4"	RIR-0825-12-YY		3"	11.1
		670	1"	RIR-0825-16-YY		3"	11.1
		670	1"	RIR-0825-16-YY-SI		3"	11.1
		670	1-1/4"	RIR-0825-20-YY		3"	11.1
		670	3/4"	RIR-0825-12		3-1/2"	11.5
		670	1"	RIR-0825-16		3-1/2"	11.5
		670	1"	RIR-0825-16-SI		3-1/2"	11.5
		670	1-1/4"	RIR-0825-20		3-1/2"	11.5
8"	3"	840	3/4"	RIR-0830-12		3-1/2"	13.0
		840	1"	RIR-0830-16		3-1/2"	13.0
		840	1"	RIR-0830-16-SI		3-1/2"	13.0
		840	1-1/4"	RIR-0830-20		3-1/2"	13.0
10"	2-1/2"	790	3/4"	RIR-1025-12-YY	RIT-1025-12-YY	3"	13.0
		790	1"	RIR-1025-16-YY	RIT-1025-16-YY	3"	13.0
		790	1"	RIR-1025-16-YY-SI		3"	13.0
		790	1-1/4"	RIR-1025-20-YY		3"	13.0
		790	3/4"	RIR-1025-12	RIT-1025-12	3-1/2"	13.0
		790	1"	RIR-1025-16	RIT-1025-16	3-1/2"	13.0
		790	1"	RIR-1025-16-SI		3-1/2"	13.0
		790	1-1/4"	RIR-1025-20		3-1/2"	13.0
10"	3"	1000	3/4"	RIR-1030-12	RIT-1030-12	3-1/2"	15.0
		1000	1"	RIR-1030-16	RIT-1030-16	3-1/2"	15.0
		1000	1"	RIR-1030-16-SI		3-1/2"	15.0
		1000	1-1/4"	RIR-1030-20		3-1/2"	15.0
10"	4"	1400	3/4"	RIR-1040-12	RIT-1040-12	4-1/2"	30.0
		1400	1"	RIR-1040-16-SI	RIT-1040-16	4-1/2"	30.0
		1400	1-1/4"	RIR-1040-20	RIT-1040-20	4-1/2"	30.0
		1400	1-1/4"	RIR-1040-20-SI		4-1/2"	30.0
		1400	1-1/2"	RIR-1040-24	RIT-1040-24	4-1/2"	30.0
11"	5"	1760	1-1/4"	RIR-1150-20	RIT-1150-20	5-1/2"	42.0
12"	2-1/2"	900	3/4"	RIR-1225-12-YY	RIT-1225-12-YY	3"	16.0
		900	1"	RIR-1225-16-YY	RIT-1225-16-YY	3"	16.0
		900	1"	RIR-1225-16-SI-YY		3"	16.0
		900	1 1/4"	RIR-1225-20-YY		3"	16.0
12"	3"	1140	3/4"	RIR-1230-12	RIT-1230-12	3-1/2"	21.0
		1140	1"	RIR-1230-16	RIT-1230-16	3-1/2"	21.0
		1140	1"	RIR-1230-16-SI		3-1/2"	21.0
		1140	1-1/4"	RIR-1230-20		3-1/2"	21.0
12"	4"	1600	1"	RIR-1240-16-SI	RIT-1240-16	4-1/2"	26.0
		1600	1-1/4"	RIR-1240-20	RIT-1240-20	4-1/2"	26.0
		1600	1-1/4"	RIR-1240-20-SI		4-1/2"	26.0
		1600	1-1/2"	RIR-1240-24	RIT-1240-24	4-1/2"	26.0
12"	5"	2050	1-1/4"	RIR-1250-20	RIT-1250-20	5-1/2"	40.0
16"	3"	1420	3/4"	RIR-1630-12	RIT-1630-12	3-1/2"	32.0
		1420	1"	RIR-1630-16	RIT-1630-16	3-1/2"	32.0
		1420	1"	RIR-1630-16-SI		3-1/2"	32.0
		1420	1-1/4"	RIR-1630-20		3-1/2"	32.0
18"	3"	1580	3/4"	RIR-1830-12	RIT-1830-12	3-1/2"	42.0
		1580	1"	RIR-1830-16	RIT-1830-16	3-1/2"	42.0
		1580	1"	RIR-1830-16-SI		3-1/2"	42.0
		1580	1-1/4"	RIR-1830-20		3-1/2"	42.0
18"	5"	2800	1-1/4"	RIR-1850-20	RIT-1850-20	5-1/2"	50.0
		2800	1-1/2"	RIR-1850-24	RIT-1850-24	5-1/2"	50.0

WHEELS
RUBBER
ENGINEERED TO OUTPERFORM
UP TO 2,800 LBS CAPACITY